

# Univox® Microphones

## Univox 13T Boundary Conference Microphone.

---

The Univox 13T is a boundary microphone fabricated in beech. It is perfect for positioning on a conference table but can also be mounted on ceilings and walls. For longer conference tables, several Univox 13T microphones can be used. To limit background noise pick up no more than four should be used simultaneously. The Univox 13T can be supplied with a 3.5 mm mini jack or a XLR connector.

Part No	241503 XLR plug
Type	Electret condenser capsule, boundary
Polar pattern	Omni-directional
Frequency range	30-15,000 Hz
Sensitivity	-53 dB re V/Pa
Bias voltage	5-15 V DC phantom power
Cord length	3 m
Connector	3.5 mm plug, stereo / XLR plug
Dimension	Ø 80 mm / H 16 mm
Weight	110 / 130 g
Colour	Beech wood casing with black cord



## Univox M-2 Goose Neck Microphone

---

The Univox M-2 is a small and elegant goose neck microphone, particularly suited to across the counter situations. The microphone's high sensitivity provides for a good speech level, even if the speaker is not close to and/or directly in front of the microphone.

Part No	241602 3.5 mm plug / 241604 XLR plug
Type	Electret condenser capsule, goose neck
Polar pattern	Omni-directional
Frequency range	50-18,000 Hz
Sensitivity	-65 dB re V/Pa
Bias voltage	9-12 V DC phantom power
Cord length	1.8 m Connector 3.5 mm plug, stereo / XLR plug
Dimension	Base Ø 80 mm / H 270 mm
Weight	300 / 320 g
Colour	Black with black cord
Accessories included	Windshield (black)



## AVLM5 Wall Mounted Microphone

---

AVLM5 is designed for use in across the counter systems such as teller windows, information centres, ticket booths and other glass partitioned environments. It can also be attached to a computer display or alike. Installation is quick and simple using the Velcro pads provided. AVLM5 has a very linear frequency pattern and an omni-directional characteristic for enhanced speech intelligibility. The elegant microphone in metal also delivers strongly reduced hum level.

Part No	242420
Type	Electret condenser capsule, attachable
Polar pattern	Omni-directional
Frequency range	50-18,000 Hz
Sensitivity	-54 dB re V/Pa
Bias voltage	6-12 V DC phantom power
Cord length	6m
Connector	3.5 mm plug, mono
Dimension	Ø 42 mm / H 15 mm
Weight	67 g
Colour	Graphite with black cord
Accessories included	Adhesive Velcro pads

